

Pebble - Promenade Slabs

Our Pebble finish is a new addition to the Castle Range of surface finishes. The Pebble finish creates an attractive, durable surface along with one of the highest slip resistance results in the range.

450 x 450 x 38mm

Pebble 450 x 450 mm Promenade Slabs are manufactured and tested in accordance with BS 1339. This ensures that our slabs are strong, durable and slip resistant and can be installed on a flatroof or balcony with complete confidence.

Our 450 x 450 mm Promenade Slabs can be laid using our range of support pads or they can be loose laid as ballast as they exceed the wind uplift requirements of 80kg per m2.

Starting at only 16kg each they are also very easy to handle and under the 25kg lifting limit recommended by the Health & Safety Executive.

The 450 x 450 Striated has a notched side wall design to accommodate the support pad lugs and keep the gaps between each slab to a minimum.



600 x 600 x 38mm

Pebble 600 \times 600 mm Promenade Slabs are manufactured and tested in accordance with BS 1339. This ensures that our slabs are strong, durable and slip resistant and can be installed on a flatroof or balcony with complete confidence.

Our 600 x 600 mm Promenade Slabs can be laid using our range of support pads or they can be loose laid as ballast as they exceed the wind uplift requirements of 80kg per m2.

The 600 x 600 Striated has a notched side wall design to accommodate the support pad lugs and keep the gaps between each slab to a minimum.

	Weight	No Per m2	Slip Resistance	EN 1339 Marking	Reaction To Fire
Striated	29kg Approx	2.8	58 WET	AIKPU7	A1
Pebble	29 kg Approx	2.8	66 WET	AIKPU7	A1

Colours below available in 600 x 600 x 38mm



Dark Grey Grey Marbled Old Gold Terracotta Terra Marbled Red Red Marbled

Please click here to contact us if you would like any more details

Technical Information



Surface	Pebble	
Length	445mm	
Width	445mm	
Thickness	38mm	
Weight	16kg	
Slip Resistance	66 Wet (Low Potential For Slip)	
BS EN 1339 Marking	AIKPU 4	

