Riven - Promenade Slabs

The Riven finish is an excellent example of the texture, warmth and practicality of natural stone combining with the durability and strength of Glass Fibre Reinforced Concrete to produce a product which gives the very best attributes of both worlds.

The use of numerous mould finishes means that the repetitive nature of some products is avoided, giving a more natural appearance.

The colours available in the Riven finish have been carefully selected to replicate natural stone colours and the wide choice gives the facility to match adjacent colour schemes.

The 22mm thick 300 x 300mm Promenade Slabs have been specially designed to be used with Paving Support Pads. They can of course still be fixed direct to the roof surface with PU Adhesive but using the Paving Support Pads allows them to be used in any situation where direct contact with the waterproofing membrane is to be avoided, such as with some of the single ply membrane manufacturers.

This system also gives the freedom of being able to remove the tiles for inspection, services, repairs and many other reasons for wishing to remove the tiles during their lifetime. The tiles are tested internally and externally and average breaking loads of 300 kg are achieved.

300 x 300 x 22mm

Colours below available in 300 x 300 x 22mm



450 x 450 x 38mm


Riven $450 \times 450 \times 38$ mm Promenade Slabs are manufactured and tested in accordance with BS 1339. This ensures that our slabs are strong, durable and slip resistant and can be installed on a flat roof or balcony with complete confidence.

Our 450×450 mm Promenade Slabs can be laid using our range of support pads or they can be loose laid as ballast as they exceed the wind uplift requirements of 80kg per m2.

Starting at only 16kg each they are also very easy to handle and under the 25kg lifting limit recommended by the Health & Safety Executive.

The 450×450 Riven has a notched side wall design to accommodate the support pad lugs and the gaps between each slab to a minimum.

Colours below available in 450 x 450 x 38mm



Technical Information



Surface	Striated
Length	445mm
Width	445mm
Thickness	38mm
Weight	16kg
	58 Wet
Slip	(Low
Resistance.	Potential
	For Slip)
BS EN	
1339	AIKPU4
Marking	

