

SPECIFICATIONS ANS GRUFE - GREEN ROOF SYSTEMS

All proposed Green Roofs are to be installed using the ANS Grufe Green Roof System[™] supplied by the ANS Group (Europe) LLP, or similar and approved. The ANS Grufe Green Roof System[™] will be supplied with established plant coverage as detailed in design, growing on 60mm ANS 100% recycled growing media. The ANS Grufe Green Roof System[™] has a saturated weight of 65kg per m².



Bio-blanket: Made from recycled polyethylene and renewable hemp fibres, and performs the following roles – water retention, filter fabric, even water distribution, root anchor layer for the planting.



grufe

- Compressive strength 2.000 Kg/m²
- Water holding capacity of 20 litres/m²
- UV resistant
- Temperature range -50°C 80°C
- Carrier material 100% Regenerated Polypropylene (PP)
- Carrier measures 540 x 540 x 90mm
- Drainage Surface 318 cm2/m²
- Outflow Volume 40 I/m²
- Saturated weight 65kg/m²
- 10 year guarantee

Vegetation: Consists of Sedum, or a mix of Sedums, Wild Flowers and grasses. Varieties are dependent upon location and project purpose, but many different design options are available.

Carrier: Made from recycled HDPE plastic, and performs the following roles – a water reservoir, drainage layer, protection from excessive drying of roots from the airspace below, the cups greatly improve product handing making it easier to install

Installation

The item is equipped with a double-action coupling system: the tabs on the side of each part engage the edge in the gaps between tabs of the facing part. **Media:** The media mix used is a special substrate prepared specifically for ANS, but particular mixes can also be prepared depending on the planting & project requirement.

www.grufe.co.uk

ansurbanruralism

ANS Group (Europe) Aldingbourne Nurseries Church Road Aldingbourne Chichester PO20 3TU +44 (0)845 505 5555 enquiries@ansgroupeurope.com urbanruralism.com