



RESITRIX<sup>®</sup> is an all-purpose, extremely durable and easy-to-install, single-ply waterproofing membrane with an EDPM surface layer. The material properties of the whole RESITRIX<sup>®</sup> range, guarantee ultimate efficiency and excellent welding characteristics, which are significantly reducing the number of workers and time needed for any roofing project.



Unit C1, M62 Trading Estate, Larsen Road, Goole, East Yorkshire, DN14 6XF Phone: 01405 780444 / 01752 559036 Fax: 01405 780445 Email: sales@meir-roofing.co.uk Website:www.meir-roofing.co.uk





SITRIX

## SR / Grey for Light Coloured Roofs

RESITRIX® SR is a light grey coloured, selfadhesive, hot-air weldable EPDM waterproofing membrane. Due to the grey colour, RESITRIX®SR offers new aesthetic design options and additionally has solar reflective properties.

**RESITRIX<sup>®</sup> SK W FULL BOND** is a fully selfadhesive and root resistant heat-weldable EPDM waterproofing membrane, which carries FLL root safe certification. RESITRIX<sup>®</sup> SK W Full Bond can be installed in a variety of applications, either fully exposed or beneath roof gardens and living roof systems.



- 20 CE

Canant

ALUTRIX<sup>®</sup> 600 is a self-adhesive vapour barrier. It is suitable for all internal conditions, including very high humidity. This vapour barrier consists of a reinforced composite aluminium foil with a tenacious self-adhesive backing and removable release film.

## MB / Mechanically Fixed

RESITRIX\* MB is a heat-weldable EPDM waterproofing membrane especially used for mechanically fixed applications. RESITRIX\* MB complies fully with all requirements of FM Approval Standard Class No. 4470



ESITRIX

## CL / Preferably for PU-Adhesion

RESITRIX<sup>®</sup> CL is the classic EPDM waterproofing membrane for hot and cold bonding applications, preferably for PU-adhesion. For decades, it has consistently proven itself in practice, on tens of thousands of flat roofs.